

Preliminary specifications<sup>1</sup>

# SMART Board® 6086S interactive display with iQ

Model SBID-6286S

## Overview

The SMART Board® 6086S interactive display with iQ and SMART Learning Suite is the hub of your classroom.

The 4K Ultra HD LED interactive display provides optimal image clarity and wide viewing angles. SMART's exclusive and proprietary ToolSense™ technology allows a wide range of accessories to cater to different subject matter, learning styles, and student needs. Unique Simultaneous Tool Differentiation allows multiple users to write simultaneously with a pen, move objects with a finger, and erase digital ink with a palm—all without switching tools, providing uninterrupted collaboration. The display's advanced HyPr Touch™ with InGlass™ touch technology provides a natural, intuitive writing and touch experience with high accuracy and low latency.


Temperature and humidity sensors help administrators provide the optimal environmental conditions for effective learning. The display's iQ embedded computing experience offers one-touch access to collaboration tools, including a digital whiteboard, a web browser, and wireless screen sharing.

See [smarttech.com](http://smarttech.com) for more information.



## Dimensions and weights<sup>2</sup>

### Dimensions



### Weight

175 lb. (79.5 kg)

Pending its certification as an ENERGY STAR® certified signage display, the SMART Board 6086S interactive display meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

<sup>1</sup>This product is in the final stages of development, and these specifications are subject to change.

<sup>2</sup>All dimensions ± 1/8" (0.3 cm). All weights ± 2 lb. (0.9 kg).

## Highlights

<b>HyPr Touch with InGlass</b>	HyPr Touch with InGlass advanced optical technology ensures highly accurate writing and drawing
<b>ToolSense</b>	ToolSense proprietary tool technology supports virtually unlimited pen and tool recognition
<b>Environmental sensors</b>	Integrated temperature and humidity sensors provide real-time measurement of the display's environmental conditions. Data is available via an included SMART app.
<b>Ambient light sensor</b>	Screen automatically dims or brightens, ensuring comfortable viewing in all lighting conditions

## Hardware

### Interaction

Touch technology	HyPr Touch with InGlass
Multitouch capabilities	Up to 20 simultaneous interaction points <sup>3</sup>
Object Awareness™	Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger, eraser, or palm
Simultaneous Tool Differentiation	Multiple users can touch the display and use pens and erasers at the same time for a natural, fully collaborative experience
Pen ID™	Multiple users can write independently and simultaneously, using different colored ink
ToolSense	Support for virtually unlimited pen and tool recognition
Silktouch™	Ultra-smooth finish that allows you to use the display for hours without finger burn

### Display

Type	LCD with LED back light
Aspect ratio	16:9
Optimal resolution (HDMI inputs)	4K UHD (3840 × 2160) at 60 Hz
Brightness (maximum)	350 cd/m <sup>2</sup>
Pixel dimensions	0.429 mm × 0.429 mm
Viewing angle	178°
Response time	8 ms
Ambient light sensor	Yes
Proximity sensor	Yes
Infrared sensor	Yes

<sup>3</sup>Chrome OS™ is limited to 10 simultaneous touches, including gestures. Automatic pen recognition, plus palm, pen, and eraser differentiation are available in supported applications.

**SMART Board 6086S interactive display with iQ – Model SBID-6286S**

Room temperature and humidity sensors	Yes
<b>100BASE-T Ethernet</b>	Two external ports for a 4-port Fast Ethernet switched network that connects the interactive display to a network and an external device, such as a computer
<b>Wi-Fi</b>	IEEE 802.11A/B/G/N/AC with 2 × 2 MIMO (both 2.4 and 5 GHz bands)
<b>Bluetooth®</b>	Bluetooth 4.2 dual mode (backwards compatible with Bluetooth 2.1 + EDR)
<b>Audio</b>	Two 20 W integrated speakers
<b>Noise level</b>	<32 dBA
<b>Included cables and accessories</b>	<ul style="list-style-type: none"> <li>1 Country-specific power cable</li> <li>1 USB cable</li> <li>2 Pens (red and black)</li> <li>2 Eraser</li> <li>1 Remote control</li> <li>2 AAA batteries for the remote control</li> <li>1 WM-SBID-200 wall mount</li> </ul>
<b>Mounting holes</b>	For a standard VESA 600 mm × 400 mm mounting plate Lower mounting holes 11" (28 cm) from the bottom of the interactive display
<b>Mounting bracket depth</b>	Minimum depth of 1 1/2" (3.7 cm) for all components on the back of the interactive display for airflow
<b>Accessory holes</b>	M4 mounting points located at the top, bottom, left, and right for SMART approved accessories
<b>iQ technology</b>	
<b>iQ experience</b>	iQ experience embedded in the display provides better performance without the need to install a separate appliance
<b>Included apps and features</b>	<ul style="list-style-type: none"> <li>Customizable Home screen</li> <li>Whiteboard</li> <li>SMART Notebook Player</li> <li>Browser</li> <li>Screen Share</li> <li>File and app libraries</li> <li>Writing and drawing over any input</li> <li>Freeze screen and screen shade</li> <li>Automatic software updates</li> </ul>

**SMART Board 6086S interactive display with iQ – Model SBID-6286S**

<b>Supported languages</b>	Chinese (simplified)
	Chinese (traditional)
	Danish
	Dutch
	English
	Finnish
	French
	German
	Italian
	Korean
	Norwegian
	Portuguese
	Russian
	Spanish
	Swedish
Ukrainian	
Vietnamese	

## Software

<b>Included software</b>	iQ Android-based embedded computing SMART Ink® and SMART Product Drivers SMART Notebook® basic version Bonus one-year subscription to SMART Learning Suite (including SMART Notebook software) Subscription to SMART Remote Management for the length of warranty
--------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Connectors



<b>Convenience panel</b>	1 HDMI® 2.0 in with HDCP 1.4 and HDCP 2.2 support
	2 USB 3.0 Type-A (for media)
	1 USB 3.0 Type-B (for touch)

---

<b>Connector panel</b>	1 Accessory slot (for OPS devices)
	1 USB 3.0 Type-A (for media)
	1 USB 2.0 Type-A (for service use only)
	3 USB 3.0 Type-B (for touch)
	2 HDMI 2.0 in with HDCP 1.4 and HDCP 2.2 support
	1 HDMI 2.0 out
	1 VGA in
	1 Stereo 3.5 mm in
	1 Stereo 3.5 mm out
	1 S/PDIF out
	2 RJ45
	1 RS-232 in
	1 RS-232 out

---

<b>Back of display</b>	1 AC power in
	1 AC power out

## Installation requirements

**Interactive display** See the *SMART Board 6000S and 6000S Pro series interactive displays installation and maintenance guide* ([smarttech.com/kb/171414](http://smarttech.com/kb/171414))

### **!** IMPORTANT

The display needs an internet connection for downloading and installing important updates. Ask the network administrator to configure the network correctly for the iQ experience. For more information about network configuration, see [Connecting a SMART display with the iQ experience to a network](#).

## Room computers and guest laptops

General requirements See [SMART Notebook software release notes](#)

4K UHD Video card that can support 3840 × 2160 resolution at 60 Hz  
See [Minimum requirements for Ultra High Definition or 4K on your interactive flat panel](#)

## Mini-computers

General requirements See [SMART Notebook software release notes](#)

Dimensions Smaller than 4 3/4" × 4 3/4" × 1 1/4" (12 cm × 12 cm × 3.3 cm)

Weight Less than 10 lb. (4.5 kg)

Mounting VESA 75 mm × 75 mm or 100 mm × 100 mm mounting pattern (two mounting points: left and right)

## Cable requirements

**HDMI** Maximum length: 23' (7 m)

### NOTES

- Use only certified HDMI cables that have been tested to support the performance standard you require.
- The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality.

**USB 2.0** USB 2.0 certified  
Hi-Speed (480 Mbps) support  
Maximum length: 16' (5 m)

**USB 3.0** USB 3.0 certified  
SuperSpeed (5 Gbps) support  
Maximum length: 9' (3 m)

### NOTES

- SMART supports only installations that use directly connected video and USB cables, AC-powered extenders, or USB extenders purchased from SMART.
- You might be able to use higher-grade cables that are longer than specified. If you have problems with such a cable or an extender of any type, test the connection with a shorter cable before contacting SMART Support.

**Important** Using cables that exceed these maximum lengths can produce unexpected results, such as degraded picture quality or USB connectivity. Refer to *Installation best practices for SMART products* ([smarttech.com/kb/171035](http://smarttech.com/kb/171035)) for comprehensive information about cables and extensions for SMART hardware products.

## Storage and operating requirements

<b>Power requirements</b>	100V to 240V AC, 50 Hz to 60 Hz
<b>Power consumption at 77°F (25°C)</b>	
Standby mode	<b>TBC</b>
Normal operating	<b>TBC</b>
<b>Operating temperature</b>	41–95°F (5–35°C)
<b>Storage temperature</b>	-4–140°F (-20–60°C)
<b>Humidity</b>	5–80% relative humidity, non-condensing

## Regulatory Certifications (Model ID: IDS686-1)

<b>U.S. / Canada</b>	FCC, ISED, UL, CONEG Packaging, California Prop 65, Conflict Minerals
<b>EU / EEA / EFTA</b>	CE, RoHS Directive, Battery Directive, Packaging Directive, WEEE Directive, REACH Regulation, POP Regulation, Radio Equipment Directive, Low Voltage Directive, CB
<b>EAEU</b>	EAC
<b>Australia / New Zealand</b>	RCM

## Purchasing information

<b>Order number</b>	
SBID-6286S	SMART Board 6086S interactive display with iQ and SMART Learning Suite
<b>Optional accessories</b>	See <a href="http://smarttech.com/accessories">smarttech.com/accessories</a>

## Warranty information

**SMART Assure warranty** Includes advanced hardware replacement and access to onsite support. Terms and conditions vary by region. Contact your local reseller or distributor for information and visit [smarttech.com/warranty](http://smarttech.com/warranty).