

PRODUCT NAME Epson EB-L610U
PRODUCT CODE V11H901053

WHAT'S IN THE BOX

EB-L610U Projector, 3m Power Cable, 1.8m Computer cable, Remote control, 2 x AA Batteries, Cable cover, Product manual. (ELPAP10 wireless lan unit is built-in)

TECHNOLOGY

Projection System RGB liquid crystal shutter projection system
LCD Panel 0.67-inch

OPTICAL

Zoom 1 - 1.6 (Optical)
50" to 500" [1.44m to 14.76m] (Zoom: Wide)
Screen Size (Standard Lens) 50" to 500" [2.35m to 23.84m] (Zoom: Tele)
Projection Distance (Standard Lens) 80" screen 2.33 m - 3.78 m
Throw Ratio 1.35 (Zoom:Wide), 2.20 (Zoom:Tele)
Projection Lens F Number 1.5 - 1.7
Projection Lens Focal Length 20.0mm - 31.8mm
Focus Method Manual



IMAGE

Colour Light Output 6,000 Lumens
White Light Output 6,000 Lumens
Resolution WUXGA
Native Aspect Ratio 16:10
Contrast Ratio 2,500,000:1
Light Source Laser Diode
LD Input Power 246W
Vertical: $\pm 30^\circ$
Keystone Correction (Standard Lens) Horizontal $\pm 30^\circ$
Vertical: $\pm 50\%$ (Manual)
Lens Shift (Standard Lens) Horizontal: $\pm 20\%$ (Manual)

CONNECTIVITY

Input: Computer 2 x D-sub 15-Pin (RGB), 1 x USB-A, 1 x USB-B (Service)
Input: Digital 2 x HDMI
Input: Audio 2 x Audio
Input: Control 1 x RS-232C
Input: Network I/O 1 x RJ45
Input: HDBaseT 1 x HDBaseT
Output: Computer 1 x D-sub 15-Pin (RGB)
Output: Audio 1 x Audio
Wireless Connectivity Included
Miracast Included
Speaker Output 1 x 10W

ADVANCED FEATURES

EPSON Projector Management (Network & Control) Yes
EPSON iProjection (Multi-PC Projection) Yes
Wireless LAN Enterprise Security Yes
Split Screen Yes
360 Degree Projection Yes
Instant Off Yes
Direct Power On/Off Yes
Kensington®-style lock provision
Wireless LAN Unit Lock
Security
Security cable hole
Dynamic Presentation
Cinema
sRGB
DICOM SIM
Colour Modes Multi-Projection

GENERAL

Dimensions D x W x H (Including feet and back cover) 339 x 440 x 136 mm

Dimensions D x W x H (Excluding feet and back cover) 304 x 440 x 120 mm
 Weight Approx. 8.5Kg
 Projector Warranty 5 Years
 Power Consumption: LD On 353W
 Power Consumption: Standby 2.0W
 Noise Level Normal/Quiet: 38/27 dB

| PRODUCT OPTIONS | Item Code | Description |
|-----------------|------------|-------------------------------------|
| | V13H134A56 | ELPAF56 Replacement Filter |
| | V12H547053 | HDBaseT Transmitter |
| | V12H731P01 | Wireless LAN Adaptor |
| | V12H003B22 | ELPMB22 Standard ceiling mount |
| | V12H526040 | ELPMB30 Low profile ceiling mount |
| | V12H003P13 | Extension Pole 668-918 mm |
| | V12H003P14 | Extension Pole 918-1,168 mm |
| | V12H002S2Y | ELPSC21B 80" Portable tripod screen |

Epson is the registered trademark of Seiko Epson Corporation. Epson ESC/P2 and Epson Stylus are trademarks of Seiko Epson Corporation. MicroDot is a trademark of Epson Australia Pty Limited. All other product names and other company names used herein are for identification purposes only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Specifications are subject to change without notice.

Equipment supplied by Epson Australia is designed to function in conjunction with genuine Epson consumables and accessories specifically configured for it.

Usage Conditions

Epson products are designed and made to give highly reliable use and long life when used according to its specifications. With any system, product or device used in situations where human life may be involved or at risk, Epson advises that you should take all necessary steps to ensure the suitability of your Epson product for inclusion in your system, and recommends that you include fail-safe procedures and redundancy support or backup equipment in your system, to maintain the maximum safety margin and optimum system reliability. Examples include but are not limited to – do not interfere with any electrical components within the device, do not use items supplied with the product for purposes other than as intended by Epson (ie mains cords, inks, CDs, plastic wrapping) and do not make modifications to the product.